

ELECTRONIC DIRECT WIRE-IN PHOTOCONTROLS

"The Performance of an Electronic Twist-lock in a Button Control"

DESCRIPTION

B Series electronic "button type" photocontrols have the same features and performance of electronic twist-lock photocontrols. Energy efficiency is maintained with tight On/Off ratios and "non-drift operation". Maintenance costs are reduced through a cool running DC circuit. Life expectancy is up to three times longer than traditional heat generating thermal relay designs. The **B Series** uses the same field proven electronic circuit design as is used in Sun-Tech high performance twist-lock photocontrols.


FEATURES

- Meets or exceeds ANSI C136.10.
- Proven DC circuit design.
- Close 1:1.5 on to off operating ratio.
- Non-chatter load break.
- Surge Protected Electronic Circuit.
- Heavy duty construction.

BENEFITS

- 12 year expected life.
- Low power consumption and extended life from "cool" operating DC circuit.
- Close ratio reduces burning hours at sunrise.
- Extended life and accuracy from non-drift operation throughout its life.
- Significantly reduced energy costs.
- Significantly reduced maintenance costs.

MECHANICAL SPECIFICATIONS



Housing:	UV stabilized, impact resistant thermal plastic.
Window:	UV inhibitive and absorbing acrylic.
Lead Wires:	#18 AWG, 12" long.
Packaging:	Individual units are sealed in water resistant plastic.
Weight:	3.0 oz. each, 20 lbs. 100 carton.
Size:	16" x 16" x 12" 100 carton.

Warranty: 6 Year 1 for 1 replacement warranty.

B Series

ELECTRONIC DIRECT WIRE-IN PHOTOCONTROLS

OPERATING SPECIFICATIONS

Operating Voltage:

<u>Model</u>	<u>Voltage</u>
B120	105 - 130
S124	105 - 305
S240	195 - 305
S480	420 - 530

Load Rating:

1000 Watt tungsten, 1800 VA

Life at rated load:

5,000 Operations (13.7 Years)

Power Consumption:

1.0 watts average @ 120 volts
1.6 watts average @ 208 volts
1.9 watts average @ 240 volts
2.1 watts average @ 277 volts

Moisture Resistance:

100% RH.

Standard Surge Protections:

- 90 Joule.
- 160 Joule.

Operating Light Levels:

+/- 0.1 fc. from specified turn-on level.
1:1.5 Average turn-on to turn-off ratio.

Photosensor:

- Conformally coated cadmium sulfide photocell.
- Encapsulated phototransistor.

Dielectric Strength:

5,000 Volts between any current carrying part.

Ambient Temperature Range:

-40°C to +70°C (-40°F to + 158°F).

CROSS REFERENCE

Sun - Tech

B120
B240
B124

Dark to Light

DB120
DB240

ORDERING INFORMATION

B120 - 1.0 - S T M

<u>Model #</u>	<u>Turn-On</u>	<u>Photosensor</u>	<u>Time Delay</u>	<u>Surge Protection</u>
<u>B120</u> (105 - 130V)	<u>1.0</u> fcs. On	<u>S</u> CdS Photocell	<u>_</u> No Delay *	<u>_</u> 90J MOV *
<u>B124</u> (105 - 305V)	<u>1.5</u> fcs. On	<u>P</u> Phototransistor	<u>T</u> 3-5 Sec. Delay	<u>M</u> 160J MOV
<u>B240</u> (195 - 305V)	<u>2.0</u> fcs. On			

* No Letter

FP *Outdoor Lighting Controls*
Quality Electrical Products

54 Commercial St. * Raynham, MA 02767 USA

Ph:(508) 821-1597 * Fax:(508) 822-0593 * email: info@sun-tech.biz * www.sun-tech.biz * www.fpolc.com